



P/500 | P/501 | P/502

POMPA DI INGRASSAGGIO A MANO | HAND OPERATED GREASE PUMP
POMPE DE GRAISSAGE A MAIN | HANDFETTPUMPE

- Pompa di ingrassaggio manuale a leva
- Serbatoio da 800-500-300 g
- P/500 e P/501 Caricamento manuale e a cartuccia
- P/502 Caricamento solo manuale
- Uscita grasso filettata M10x1
- Pompe graissage manuelle à levier
- Réservoir de 800-500-300 g
- P/500 et P/501 Chargement manuel et à cartouche
- P/502 Chargement uniquement manuel
- Sortie graisse fileté M10x1
- Hand operated grease pump with lever
- 800-500-300 g tank
- P/500 and P/501 manual refill and with cartridge
- P/502 only with manual refill
- M10x1 threaded grease output
- Handfettpumpe mit Hebel
- Behälter 800-500-300 g
- P/500 und P/501 manuelle Befüllung und mit Kartusche
- P/502 nur mit manueller Befüllung
- Fettausgang mit Gewinde M10x1



COD.	MOD.	CAPACITÀ CAPACITY	F	Ø CORPO BODY	LUNGHEZZA LENGTH	CARTUCCIA CARTRIDGE		
AH090101	P/500	800 g	M10x1	Ø57	350	Ø52 cc. 600	1	1355
AH090201	P/501	500 g	M10x1	Ø57	290	Ø52 gr. 400	1	1268
AH090301	P/502	300 g	M10x1	Ø46	200	- - -	1	787

SN/1

SNODO | SWIVEL | ROTULE | GELENK

- Giunto snodabile triplo in acciaio zincato
- Guarnizioni PTFE / NBR
- Max. Pres. 600 bar
- Joint articulé triple en acier zingué
- Joints PTFE / NBR
- Max. Pres. 600 bar
- Zinc-plated steel triple swivel
- NBR/PTFE seals
- Max. Pres: 600 bar
- 3-faches Gelenk aus verzinktem Stahl
- Dichtungen aus PTFE/NBR
- Max. Druck 600 bar



COD.	MOD.	F		
BH098876	SN/1	1/4M - 1/4F	1	185

SN/2

SNODO | SWIVEL | ROTULE | GELENK

- Giunto snodabile in acciaio zincato
- Guarnizioni PTFE / NBR
- Max. Pres. 600 bar
- Joint articulé en acier zingué
- Joints PTFE / NBR
- Max. Pres. 600 bar
- Zinc-plated steel swivel
- NBR/PTFE seals
- Max. Pres: 600 bar
- Gelenk aus verzinktem Stahl
- Dichtungen aus PTFE/NBR
- Max. Druck 600 bar



COD.	MOD.	F		
BH098907	SN/2	1/4M - 1/4F	1	80