


205-..., 205A-..., 205W-...

COMBINATION SPANNER

- long version, both ends fit same nut size
- cranked
- size 5 mm: ring side in hexagon
- up to 34 mm, 1.1/4" AF, 3/4" WW:
jaw polished, shaft matt chrome plated,
all further sizes matt chrome plated
- ELORA-Chrome-Vanadium 31CrV3 / 1.2208
- according to DIN 3113, Form B, ISO 3318, ISO 7738



Code	Number	l/mm	h1 (max.) mm	h2 (max.) mm	t1 (max.) mm	t2 (max.) mm	Pieces	Weight/g
0205000051000	205-5	123	16,5	10,0	4,4	6	12	20
02050000551001	205-5,5	123	16,5	10,0	4,4	6	12	20
0205000061000	205-6	127	18,0	11,0	4,4	6,9	12	20
0205000071000	205-7	127	18,0	12,5	4,4	6,9	12	22
0205000081000	205-8	139	20,5	14,0	4,7	7,5	12	30
0205000091000	205-9	144	22,5	15,5	4,7	8,1	12	40
0205000101000	205-10	149	24,0	16,5	5,2	8,5	12	40
0205000111000	205-11	162	27,0	18,5	5,3	9,3	12	60
0205000121000	205-12	170	29,0	19,5	5,4	9,8	6	75
0205000131000	205-13	177	30,0	21,0	5,8	10,2	6	75
0205000141000	205-14	194	33,0	22,5	6,3	10,9	6	88
0205000151000	205-15	214	35,5	25,5	6,7	11,7	6	120
0205000161000	205-16	214	35,5	25,5	6,7	11,7	6	120
0205000171000	205-17	234	39,0	27,0	7,2	12,7	6	150
0205000181000	205-18	245	41,0	28,5	7,6	13,3	6	160
0205000191000	205-19	256	41,0	30,0	7,6	13,3	6	190
0205000201000	205-20	274	45,0	33,0	8,0	14,2	6	220
0205000211000	205-21	274	45,0	33,0	8,0	14,2	6	220
0205000221000	205-22	295	48,0	34,5	8,4	15,0	6	290
0205000231000	205-23	319	51,0	37,0	9,0	15,9	3	325
0205000241000	205-24	319	51,0	37,0	9,0	15,9	3	325
0205000251000	205-25	344	55,0	39,0	9,7	17,0	3	390
0205000261000	205-26	344	55,0	39,0	9,7	17,0	3	390
0205000271000	205-27	369	60,0	43,0	10,4	18,5	3	510
0205000281000	205-28	369	60,0	43,0	10,4	18,5	3	510
0205000291000	205-29	394	64,0	45,0	11,2	19,6	3	605
0205000301000	205-30	394	64,0	45,0	11,2	19,6	3	605
0205000321000	205-32	419	69,0	48,0	11,7	20,7	3	770
0205000331000	205-33	419	69,0	48,0	11,7	20,7	3	770
0205000341000	205-34	419	69,0	48,0	11,7	20,7	3	770
0205000361000	205-36	459	77,0	55,0	12,7	22,9	3	950
0205000381000	205-38 / 1.1/2	459	77,0	55,0	12,7	22,9	3	950
0205000411000	205-41 / 1.5/8	509	86,0	61,0	13,7	24,9	3	1350
0205000461000	205-46 / 1.13/16	521	93,0	66,0	14,7	25,8	1	1750
0205000501000	205-50	560	104,0	74,0	16,7	26,6	1	2225
0205000551000	205-55	570	112,0	82,0	19,6	29,0	1	2640
0205000601000	205-60	660	122,0	88,0	21,0	32,0	1	3700
0205000651000	205-65	710	130,0	97,0	23,0	34,0	1	4600
0205000701000	205-70	760	142,0	104,0	25,0	36,0	1	5600
0205000751000	205-75	810	150,0	110,0	27,0	40,0	1	6600
0205000801000	205-80	855	160,0	116,0	30,0	45,0	1	8900



Code	Number	l/mm	h1 (max.) mm	
0205100131000	205A-1/4	127	18,5	
0205100171000	205A-5/16	139	20,5	
0205100181000	205A-11/32	144	22,5	
0205100191000	205A-3/8	149	24,0	
0205100211000	205A-7/16	162	27,0	
0205100231000	205A-1/2	177	30,0	
0205100241000	205A-9/16	194	33,0	
0205100251000	205A-19/32	214	35,5	
0205100261000	205A-5/8	214	35,5	
0205100271000	205A-11/16	234	39,0	
0205100281000	205A-3/4	256	41,0	
0205100301000	205A-13/16	274	45,0	
0205100311000	205A-7/8	295	48,0	
0205100321000	205A-15/16	319	51,0	
0205100341000	205A-1	344	55,0	
0205100351000	205A-1.1/16	369	60,0	
0205100361000	205A-1.1/8	369	60,0	
0205100371000	205A-1.3/16	394	64,0	
0205100381000	205A-1.1/4	419	69,0	
0205100391000	205A-1.5/16	419	69,0	
0205100401000	205A-1.3/8	459	77,0	
0205100411000	205A-1.7/16	459	77,0	
0205000381000	205-38 / 1.1/2	459	77,0	
0205000411000	205-41 / 1.5/8	509	86,0	
0205100451000	205A-1.11/16	509	86,0	
0205100461000	205A-1.3/4	521	93,0	
0205000461000	205-46 / 1.13/16	521	93,0	
0205100481000	205A-1.7/8	521	93,0	
0205100491000	205A-2	560	104,0	
0205100501000	205A-2.1/16	560	104,0	
0205100511000	205A-2.1/8	570	112,0	
0205100521000	205A-2.3/16	570	112,0	
0205100531000	205A-2.1/4	570	112,0	
0205100551000	205A-2.3/8	660	122,0	
0205100571000	205A-2.1/2	710	130,0	
0205100581000	205A-2.9/16	710	130,0	
0205100601000	205A-2.3/4	760	142,0	
0205100631000	205A-3	810	150,0	
0205100651000	205A-3.1/4	855	160,0	



02



	h2 (max.) mm	t1 (max.) mm	t2 (max.) mm	Pieces 	Weight/g 	Code	Number	l/mm 	h1 (max.) mm	h2 (max.) mm	t1 (max.) mm	t2 (max.) mm	Pieces 	Weight/g 
	11,4	4,4	6,9	12	20	0205200061000	205W-1/8	144	22,5	15,5	4,7	8,1	12	40
	14,0	4,7	7,5	12	30	0205200091000	205W-3/16	162	27,0	18,5	5,3	9,3	12	60
	15,5	4,7	8,1	12	40	0205200131000	205W-1/4	177	30,0	21,0	5,8	10,2	6	72
	16,5	5,2	8,5	12	40	0205200171000	205W-5/16	214	35,5	25,5	6,7	11,7	6	120
	18,5	5,3	9,3	12	60	0205200191000	205W-3/8	245	41,0	28,5	7,6	13,3	6	175
	21,0	5,8	10,2	6	72	0205200211000	205W-7/16	274	45,0	33,0	8,0	14,2	6	220
	22,5	6,3	10,9	6	88	0205200231000	205W-1/2	319	51,0	37,0	9,0	15,9	3	325
	25,5	6,7	11,7	6	120	0205200241000	205W-9/16	344	55,0	39,0	9,7	17,0	3	390
	25,5	6,7	11,7	6	120	0205200261000	205W-5/8	369	60,0	43,0	10,4	18,5	3	510
	27,0	7,2	12,7	6	150	0205200271000	205W-11/16	394	64,0	45,0	11,2	19,6	3	605
	30,0	7,6	13,3	6	175	0205200281000	205W-3/4	419	69,0	48,0	11,7	20,7	3	770
	33,0	8,0	14,2	6	220	0205200311000	205W-7/8	459	77,0	55,0	12,7	22,9	3	950
	34,5	8,4	15,0	6	290	0205200321000	205W-15/16	509	86,0	61,0	13,7	24,9	3	1350
	37,0	9,0	15,9	3	325	0205200341000	205W-1	509	86,0	61,0	13,7	24,9	3	1340
	39,0	9,7	17,0	3	390									
	43,0	10,4	18,5	3	510									
	43,0	10,4	18,5	3	510									
	45,0	11,2	19,6	3	605									
	48,0	11,7	20,7	3	770									
	48,0	11,7	20,7	3	770									
	55,0	12,7	22,9	3	950									
	55,0	12,7	22,9	3	950									
	55,0	12,7	22,9	3	950									
	61,0	13,7	24,9	3	1350									
	61,0	13,7	24,9	3	1340									
	66,0	14,7	25,8	1	1750									
	66,0	14,7	25,8	1	1750									
	66,0	14,7	25,8	1	1750									
	74,0	16,7	26,6	1	2200									
	74,0	16,7	26,6	1	2200									
	82,0	19,6	29,0	1	2900									
	82,0	19,6	29,0	1	2900									
	82,0	19,6	29,0	1	2900									
	88,0	21,0	32,0	1	3900									
	97,0	23,0	34,0	1	4700									
	97,0	23,0	34,0	1	4700									
	104,0	25,0	36,0	1	5600									
	110,0	27,0	40,0	1	6600									
	116,0	30,0	45,0	1	7500									