

Universal Service Gauges

Suitable for cars and commercial vehicles, it is fitted with an extra-large filter to protect the quality mechanism, and is supplied carton packed.

FEATURES

Engineered for hard usage over a long period

Fitted with extra large filter to protect the quality mechanism

Suitable for all cars and commercial vehicles

PART NUMBER	DESCRIPTION	HEAD TYPE	CALIBRATION	RESOLUTION
TPG57H03	Chrome plated tubing with lanyard ring	Twin	10-160 lbf/in ² & 0.8-11 bar	2 lb & 0.2 bar units
TPG60H03	Heavy duty black vulcanite handle	Twin	10-160 lbf/in ² & 0.8-11 bar	2 lb & 0.2 bar units



Air Tools

Air Tool Accessories

Nitrogen Inflation Equipment

Tyre Inflation Equipment

Tyre Care

Workshop Accessories

Hose

Hose Fittings

Couplings & Adaptors

Twin Head Tyre Gauge

With its hard-wearing black vulcanite handle, the TPG54 is designed to withstand continual heavy usage. Suitable for use with the standard (8v1) and large bore (12v1) tyre valves.

FEATURES

Black vulcanite handle to withstand continual hard usage

Suitable for use with standard (8v1) and large bore (12v1) tyre valves

PART NUMBER	HEAD TYPE	CALIBRATION	RESOLUTION
TPG54H03	8v1 & 12v1	50-300 lbf/in ² & 4-20 bar	5 lb & 0.2 bar units

Also available: [RPR1H02](#) - Reconditioning and recalibration service (including a certificate of conformity)



Digital Universal Service Gauge

This Digital Universal Service Gauge is self-calibrating and features a 90 second auto power off. Easy to use - simply press the button and wait for the beep, the gauge is then ready to use.

FEATURES

4 selectable calibration options

Replaceable battery

Swivel head to allow easy access to the tyre valve

Red backlit screen for easy reading in dark or low light areas

Clear large display

PART NUMBER	HEAD TYPE	CALIBRATION	RESOLUTION
DUSG1	Angled	0-170 lbf/in ² / 0-12 bar / 0-1200 kPa / 0-12 kg/cm ²	+/- 1%



TyreCheck

TyreCheck is the professionals choice of dial pressure gauge for fast, clear and accurate readings.

FEATURES

Dial gauge, accurate and easy to read

Impact absorbing rubber outer casing

Integral swivel fitting on Twin Hold-on, for ease of use

Choice of 2 sizes - 63 mm and 80 mm diameter dials

PART NUMBER	CALIBRATION	RESOLUTION	DIAL DIAMETER (mm)	TYRE VALVE CONNECTION
DPG1H03	0-170 lbf/in ² & 0-12 bar	2 lb & 0.1 bar units	63	Twin Hold-on
DPG1H08	0-170 lbf/in ² & 0-12 bar	2 lb & 0.1 bar units	63	Euro Hold-on
DPG3H03	0-170 lbf/in ² & 0-12 bar	2 lb & 0.1 bar units	80	Twin Hold-on
DPG3H08	0-170 lbf/in ² & 0-12 bar	2 lb & 0.1 bar units	80	Euro Hold-on

Available in a wide range of calibrations

