

FASTENING TOOL IMPACT WRENCH

■ 3/4" (19mm) SQ.DR.

KW-L17G

Drive Size	3/4 in.	19.0 mm
Bolt Capacity	3/4 in.	19.0 mm
Free Speed	6,500 r.p.m.	
Length (w/o socket)	12-5/16 in.	312.0 mm
Weight (w/o socket)	11.9 lbs.	5.4 kg
Air Consumption (normal)	21.2 c.f.m.	0.60 m³/min
Hose Size	1/2 in.	12.7 mm
Anvil Length	1-7/16 in.	36.0 mm

※Performance figures are at 0.62MPa(Pe)(90PS.I.)air pressure.

Oil Bath Impact Wrench
Double Hammer



■ 3/4" (19mm) SQ.DR.

KW-L17GV

Oil Bath Anti-Vibration Impact
Wrench
Double Hammer



Drive Size	3/4 in.	19.0 mm
Bolt Capacity	3/4 in.	19.0 mm
Free Speed	6,500 r.p.m.	
Length (w/o socket)	14-7/8 in.	378.0 mm
Weight (w/o socket)	13.9 lbs.	6.3 kg
Air Consumption (normal)	21.2 c.f.m.	0.60 m³/min
Hose Size	1/2 in.	12.7 mm
Anvil Length	1-7/16 in.	36.0 mm

※Performance figures are at 0.62MPa(Pe)(90PS.I.)air pressure.

■ 3/4" (19mm) SQ.DR.

KW-L20G

Drive Size	3/4 in.	19.0 mm
Bolt Capacity	7/8 in.	22.0 mm
Free Speed	4,500 r.p.m.	
Length (w/o socket)	13-3/16 in.	334.0 mm
Weight (w/o socket)	15.8 lbs.	7.2 kg
Air Consumption (normal)	21.2 c.f.m.	0.60 m³/min
Hose Size	1/2 in.	12.7 mm
Anvil Length	1-1/2 in.	38.0 mm

※Performance figures are at 0.62MPa(Pe)(90PS.I.)air pressure.

Oil Bath Impact Wrench
Double Hammer



■ 3/4" (19mm) SQ.DR.

KW-20GI

Choice of Inside/
Outside Trigger Handle.
Single Hammer



Drive Size	3/4 in.	19.0 mm
Bolt Capacity	7/8 in.	22.0 mm
Free Speed	3,800 r.p.m.	
Impact Per Min.	1,100 i.p.m.	
Recommended Torque	190-640 ft-lb	250-870 Nm
Maximum Torque	640 ft-lb	870 Nm
Length (w/o socket)	12-15/16 in.	328.0 mm
Weight (w/o socket)	13.9 lbs.	6.3 kg
Air Consumption (normal)	21.2 c.f.m.	0.60 m³/min
Hose Size	3/8 in.	9.5 mm
Anvil Length (KW-20GI)	1-1/4 in.	31.0 mm
Anvil Length (KW-20GI-G)	6-11/16 in.	169.0 mm

※Performance figures are at 0.62MPa(Pe)(90PS.I.)air pressure.

■ 1" (25.4mm) SQ.DR.

KW-385G

Drive Size	1 in.	25.4 mm
Bolt Capacity	1-1/2 in.	38.0 mm
Free Speed	4,000 r.p.m.	
Impact Per Min.	700 i.p.m.	
Recommended Torque	250-1,010 ft-lb	340-1,370 Nm
Maximum Torque	1,180 ft-lb	1,600 Nm
Length (w/o socket)	14-3/8 in.	365.0 mm
Weight (w/o socket)	20.2 lbs.	9.4 kg
Air Consumption (normal)	25.8 c.f.m.	0.73 m³/min
Hose Size	1/2 in.	12.7 mm
Anvil Length	1-7/16 in.	36.0 mm

※Performance figures are at 0.62MPa(Pe)(90PS.I.)air pressure.

Choice of Inside/
Outside Trigger Handle.
Swing Hammer



■ 1" (25.4mm) SQ.DR.

KW-385GL

Choice of Inside/
Outside Trigger Handle.
Swing Hammer



Drive Size	1 in.	25.4 mm
Bolt Capacity	1-1/2 in.	38.0 mm
Free Speed	4,000 r.p.m.	
Impact Per Min.	700 i.p.m.	
Recommended Torque	250-1,010 ft-lb	340-1,370 Nm
Maximum Torque	1,180 ft-lb	1,600 Nm
Length (w/o socket)	20-11/16 in.	525.0 mm
Weight (w/o socket)	22.2 lbs.	10.1 kg
Air Consumption (normal)	25.8 c.f.m.	0.73 m³/min
Hose Size	1/2 in.	12.7 mm
Anvil Length	7-3/4 in.	196.0 mm

※Performance figures are at 0.62MPa(Pe)(90PS.I.)air pressure.

■ 1" (25.4mm) SQ.DR.

KW-420G

Drive Size	1 in.	25.4 mm
Bolt Capacity	1-5/8 in.	42.0 mm
Free Speed	3,000 r.p.m.	
Impact Per Min.	600 i.p.m.	
Recommended Torque	370-1,550 ft-lb	500-2,100 Nm
Maximum Torque	1,740 ft-lb	2,350 Nm
Length (w/o socket)	15 in.	381.0 mm
Weight (w/o socket)	28.8 lbs.	13.1 kg
Air Consumption (normal)	28.9 c.f.m.	0.82 m³/min
Hose Size	1/2 in.	12.7 mm
Anvil Length	1-7/16 in.	35.0 mm

※Performance figures are at 0.62MPa(Pe)(90PS.I.)air pressure.

Choice of Inside/
Outside Trigger Handle.
Swing Hammer



■ 1" (25.4mm) SQ.DR.

KW-420GL

Choice of Inside/
Outside Trigger Handle.
Swing Hammer



Drive Size	1 in.	25.4 mm
Bolt Capacity	1-5/8 in.	42.0 mm
Free Speed	3,000 r.p.m.	
Impact Per Min.	600 i.p.m.	
Recommended Torque	370-1,550 ft-lb	500-2,100 Nm
Maximum Torque	1,740 ft-lb	2,350 Nm
Length (w/o socket)	22-3/4 in.	577.0 mm
Weight (w/o socket)	31.0 lbs.	14.1 kg
Air Consumption (normal)	28.9 c.f.m.	0.82 m³/min
Hose Size	1/2 in.	12.7 mm
Anvil Length	9-1/16 in.	230.0 mm

※Performance figures are at 0.62MPa(Pe)(90PS.I.)air pressure.